

Technisch Specificatieblad Ferney Group BV

Ferney Group BV
Ampèrestraat 15
1704 SM Heerhugowaard
Nederland


Datum: 06-05-2013
TSFK 13/1526141 t/m 1526146
Rev : A
Blad : 1/2

Kelfort®

Productnaam: Kelfort® waterslang Kel-Plus

Opgesteld door: J.S.	Bekrachtigd door: W.A.
----------------------	------------------------

-
- Het product:** Kelfort® waterslang Kel-Plus is een sterke, 5-laags, no-torsion waterslang, dus knikt niet. De slang is slijtvast en heeft een lange levensduur.
- De toepassing:** Deze slang is geschikt voor transport van zowel water als voedingsstoffen.
- Eigenschappen:** Kelfort® waterslang Kel-Plus is een kwaliteitsproduct met de volgende eigenschappen:
- Geschikt voor water en voedingstoffen.
 - Robuust.
 - Flexibel, no-torsion (NTS).
 - Slijtvast, lange levensduur.
 - Vervaardigd uit niet-giftige grondstoffen.
 - Algenwerend.
 - Bestand tegen temperaturen van -20 °C tot +60 °C.
 - Weekmakervrij.
 - **Voldoet aan de Europese richtlijnen voor de voedingsmiddelenindustrie, t.w. 2002/72/EC, 2007/19/EC en modificaties. Zie bijgaande 'Declaration of compliance for materials and articles intended to come into contact with food'.**



Technisch Specificatieblad Ferney Group BV

Ferney Group BV
Ampèrestraat 15
1704 SM Heerhugowaard
Nederland

Datum: 06-05-2013
TSFK 13/1526141 t/m 1526146
Rev : A
Blad : 2/2

Kelfort®

Productnaam: Kelfort® waterslang Kel-Plus

Technische gegevens:

Materiaal: PVC, 5-laags.
Drukbestendig: 22 tot 30 bar, afhankelijk van het type waterslang.
Temperatuurbestendigheid: -20 °C tot +60 °C.
UV-bestendigheid: Ja.

Leveringsvorm:

Kleur: Rood.
Verpakking: Rol.
Afmetingen overdoos: (l x b x h): 40 x 40 x 50 cm.
Aantal dozen op pallet: 12 dozen.

De artikelnummers,

de types en de

EAN-codes:

1526141=> **25 m, 1/2", 30 bar** => 8714678039669 (rol)
1526141 8714678083990 (doos à 5 rol)
1526142=> **50 m, 1/2", 30 bar** => 8714678039676 (rol)
1526142 8714678084003 (doos à 3 rol)
1526143=> **25 m, 3/4", 24 bar** => 8714678039683 (rol)
1526143 8714678084010 (doos à 2 rol)
1526144=> **50 m, 3/4", 24 bar** => 8714678039690 (rol)
1526144 8714678084027 (pallet à 16 rol)
1526145=> **25 m, 1", 22 bar** => 8714678039706 (rol)
1526145 8714678084034 (pallet à 24 rol)
1526146=> **50 m, 1", 22 bar** => 8714678039720 (rol)

Bijlage

DECLARATION OF COMPLIANCE FOR MATERIALS AND ARTICLES INTENDED TO COME INTO CONTACT WITH FOOD

1. We hereby certify that the supplied hose NTS WHITE PLUS

(notes and/or simulants used in the migration tests, as indicated in point 3 of this declaration, allow to determine foodstuffs which may come into contact with the product according to the Directive 85/572/EC and D.M. 26/04/1993, n°. 220 and following revisions and amendments)

complies

with all relevant regulations, and particularly with the following:

- Regulation 1935/2004/EC,
- Regulation 1895/2005/EC,
- Directive 2002/72/EC, 2007/19/EC and following amendments,
- Regulation 10/2011⁽¹⁾,

⁽¹⁾Compliance referred to above mentioned Directives which will be still in force up to the 31st of December 2015 for transitional provision.

and with the following Italian Regulations:

- D.M. 21/03/1973 and following revisions and amendments,
- DPR 777/82 and following revisions and amendments.

2. The abovementioned product is manufactured with the following materials suitable for food contact:

- Inside layer made of PVC plasticized (contact side).
- Reinforcement in polyester thread.
- Outside layer made of PVC plasticized.

3. We certify that:

- The article meets the overall and specific migration limits under the following test condition:
 - Simulant A: WATER (for aqueous foodstuff).
Testing time and temperature: 10 days at 40°C.

The product complies with the overall migration limits and other specific restrictions under which the monomers and/or additives contained in the material can be submitted, at the abovementioned usage conditions. All declared is supported by analytical tests carried out in compliance with the DM 21/03/1973 or based on calculations made taking into account the % of the substances submitted to migration limits in

the test conditions. Calculations presume that 1 kg of food enters into contact with 6 dm² of product. We remind that the Migration Limit is 60 mg/Kg food [ppm], also expressed as 10 mg/dm² (if the certificate reports mg/kg it is possible to convert it into mg/dm² dividing the value by 6) and we underline that the change in the analytical tolerance is between 10 and 20% (12 mg/kg or 2 mg/dm²).

4. We suggest giving notice to the writing Society if the usage conditions of the product do not correspond to the advice here supplied or whether the foodstuff which come into contact with the product (Food Contact Material) is different from the applicable conditions and from the simulants listed above.
5. The user of the product which is intended to come into contact with food has the responsibility of informing the writing Company about any restriction due to particular component characteristics (additives and aromas) of the foodstuff which has to be transported.
6. This declaration complies with art. 16 of the 1935/2004/EC Regulation.
7. Industrial or commercial usage of the product concerned in this declaration is subject to the evaluation of its compliance to actual regulations and to the technological suitability to the declared final usage.
8. This declaration is valid as from the date indicated below and will be renewed when substantial changes in the processing (final product/raw material) will bring about modifications in some necessary requirements or when new amendments to the regulations mentioned at point 1) will require new controls to verify the compliance.
9. Moreover, we inform that all necessary support documents are at the disposal of the control authorities, in accordance with art. 16, par. 1 of Regulation 1935/2004/EC.
10. Declaration Code: 13LA00172.

This document and its attachments are addressed solely to the person or company above and contain confidential information.

Date: 14/01/2013